

ARIZONA | SHOWER DOOR

Sedona Series

Installation Instructions

THESE INSTRUCTIONS ARE FOR STANDARD INSTALLATION USING 3/8" GLASS.
PROFESSIONAL INSTALLATION RECOMMENDED.

IMPORTANT NOTE: SEDONA SERIES SHOWER ENCLOSURES ARE MEANT TO BE INSTALLED WITH THE DOOR TO THE INSIDE OF THE SHOWER OPENING, WITH THE SLIDING GLASS DOOR CLOSING TO THE WALL THE SHOWER HEAD IS LOCATED ON. WHILE CANYON SERIES SHOWER ENCLOSURES MAY BE INSTALLED IN REVERSE, THE SLIDING DOOR MUST THEN BE MOUNTED ON THE OUTSIDE. THIS WILL RESULT IN EXPOSED SCREW HEADS AND UNDESIRABLE PERFORMANCE. IF UNIT IS INSTALLED IN REVERSE, YOU MAY REQUIRE ADDITIONAL SEALS. ADDITIONAL SEALS SOLD SEPARATELY.




It is recommended that this unit be professionally installed. The nature of this install requires 2 people.

STANDARD SEDONA 180° KIT INCLUDES:

- a) 1 - Header Support Bar
- b) 4 - Rollers
- c) 2 - Stoppers
- d) 2 - Wall to Bar Fittings
- e) 2 - Glass to Bar Fittings for Fixed Panel
- f) 1 - 8" Back to Back Ladder Style Thru-Glass Pull
- g) 1 - Door Guide
- h) 1 - Length of U-Channel (Fixed Panel Support)
- i) 1 - Sleeve Over Bulb Seal for Door
- j) 1 - Dam Strip (Use of Dam Strip is Optional, However Recommended)
- k) 1 - Poly Splash Guard
- l) 1 - Bottom Drip Rail Sweep


a) Header Support Bar




b) Roller



c) Stopper



d) Wall to Bar Fitting



e) Glass to Bar Fitting For Fixed Panel




f) 8" Back to Back Ladder Style Pull



g) Door Guide




h) U-Channel



i) Sleeve Over Bulb Seal



j) Dam Strip



k) Poly Splash Guard



l) Bottom Drip Rail Sweep



ARIZONA SHOWER DOOR

- 1) Install sweep on door panel. Measure width of door panel and add $3/8"$. Cut sweep to this dimension. Install sweep to bottom of door with soft fin portion facing towards the inside of the shower and $3/8"$ hanging past handle side of door.
- 2) Install bulb seal to edge of handle side of door panel. The bulb seal is designed to sit on top of sweep previously installed.
- 3) Once sweep and bulb seal are installed set door inside shower on blocks with handle side of panel on the same side as shower head.
- 4) Attach one set of rollers to the top two holes for the sliding door glass. The rollers should be adjusted to the center of their "out of round" position. This allows for adjusting the rollers more easily if needed. Place door inside shower pan resting glass on soft blocks or blanket.
- 5) The header support bar is designed to be positioned in line with the exact center of the curb (minimum curb width of $2-15/16"$). To locate the holes in the vertical walls for mounting the header support bar, take the intended overall height to the top of the glass and deduct $4"$. This figure will represent the height location from the curb to the center of the holes to be drilled in the vertical walls. Note: Due to the extremely smooth nature of rollers, the header support bar must be installed level. **Failure to do so could result in a sliding door that rolls to one side by itself!** Drill the holes and mount the track holder fitting blocks to each side wall.
- 6) From the center of the wall to bar fitting, measure $15/16"$ towards the outside of the curb. This will determine the center-line of your fixed panel support.
- 7) Fasten the fixed panel support to the curb and wall.
- 8) Install fixed panel glass, making sure to plumb and level the glass at the intended height.
- 9) Holes in the fixed panel glass must align with pre-tapped holes in the header support bar. Please note: Both ends of the header support bar will have to be cut in order to achieve this. Measure from the center of either hole to the vertical fixed panel wall and deduct $7/8"$. Cut the header support bar (be sure cut measurement is taken from same hole used in previous step). Once that end of the header support bar is cut, measure the wall-to-wall tight dimension where the track is to be mounted. Deduct $1\ 3/4"$ and cut the opposite side of the header support bar. Please note: the header support bar is made of stainless steel. Special cutting tools would be used such as a stainless steel tubing cutter. Hand held hacksaw is not recommended.
- 10) The header support bar is to be permanently mounted. Prior to permanently mounting the header support bar, slide a stopper on each end (with the rubber bumper portion toward the ceiling), then slide a glass to bar fitting for wall on each end (set screws facing to the floor). Carefully place the header support bar between the wall to bar fitting.

ARIZONA SHOWER DOOR

- 11) Slide both wall to bar fittings from the header support bar to the blocks mounted to the wall making sure pre-tapped holes in bar line up with the holes in the fixed panel glass. Tighten the top and bottom set screws closest to the wall to hold the track holder fittings tightly to the mounting blocks. Tighten remaining set screws in both track holder fittings to securely fix header support bar in place.
- 12) Before permanently fastening the fixed panel to the header, carefully slide the stopper on the fixed panel side of the header support bar to a midway position between the first hole and the far end of the fixed panel wall.
- 13) With the fixed panel in place, fasten the glass to bar fittings for the fixed panel, attaching the glass to the header support bar.
- 14) Place the guide in the correct position and mark the base/curb for drilling. Guide is designed to slide over u-channel at the end of the fixed panel. Mount the guide.
- 15) Carefully hang the door on the top of the header support bar, placing the glass inside the guide. Slowly roll the door to check for the correct fit and adjust the rollers if needed.
- 16) Fasten the second (lower) set of rollers through the door glass. Adjust the second set of rollers, allowing them to ride 1/16" below the header support bar. The second set of rollers is merely an anti-lift feature and is not intended to roll.
- 17) With the sliding glass door in the closed position, adjust stopper to top roller and tighten set screws.
- 18) Attach back to back ladder style thru-glass pull.
- 19) Slide door to open position, leaving at least 2" between the handle and the fixed panel. Adjust remaining stopper and tighten set screws.
- 20) Measure from the wall to the edge of door guide to determine length of the dam strip. Cut and install dam strip directly in line with fixed panel using either a shower approved double stick tape, or silicone.
- 21) Clean glass thoroughly.
- 22) Seal glass to wall/channel with silicone and allow the enclosure to cure for 24 hours before use.